

LOGO! TD TEXTDISPLAY, 6 LINES, 3 BACKGROUND COLORS 2
ETHERNET PORTS ACCESSORIES, FOR LOGO! 8



General information

Application area	Can be used with LOGO! 8 and higher
Delivery quantity in pieces	1

Operator control and monitoring

Illuminant	LED
------------	-----

Display

Design of display	FSTN
graphics-enabled	No
Line display	
• Number of lines	6
• Number of characters per line	24

Control elements

Keyboard	
• Keys with LED	No
• System keys	Yes
— Number of configurable system keys	0
• Numeric/alphabetical input	
— Numeric keyboard	No

— Alphanumeric keyboard	No
Installation type/mounting	
Wall mounting/direct mounting possible	No
Supply voltage	
Type of supply voltage	AC/DC
Rated value (DC)	12 V; 12 V DC, 12/24 V AC/DC
permissible range, lower limit (DC)	10.2 V
permissible range, upper limit (DC)	28.8 V
Power losses	
Power loss, typ.	1.8 W; Typical
Digital inputs	
Number of digital inputs	0
Interfaces	
Number of RS 232 interfaces	0
Number of other interfaces	0
Industrial Ethernet	
• Number of industrial Ethernet interfaces	2
Interrupts/diagnostics/status information	
Diagnostic messages	
• Diagnostic functions	No
Diagnostics indication LED	
• Status indicator digital input (green)	No
Standards, approvals, certificates	
CE mark	Yes
KC approval	Yes
UL approval	Yes
FM approval	Yes
Marine approval	
• American Bureau of Shipping (ABS)	Yes
Ambient conditions	
Operating temperature	
• Min.	0 °C
• max.	55 °C
Accessories	
belongs to product	LOGO!
Mechanics/material	
Design of housing	plastic
Type of housing (front)	plastic
• plastic	Yes
Dimensions	

Width	128.2 mm
Height	86 mm
Depth	38.7 mm

Weights

Weight, approx.	220 g
-----------------	-------

Scope of supply

Delivery unit in items	1
last modified:	24.10.2014